Ecological and economic optimization of iron ore processing automated control



Vladimir Morkun

Vice-Rector for research, Doctor of Science, Professor, Head of Computer Science, Automation and Control Systems department State Higher Educational Institution "Kryvyi Rih National University", Ukraine



Vitaliy Tron

PhD, Senior lecturer of Computer Science, Automation and Control Systems department State Higher Educational Institution "Kryvyi Rih National University", Ukraine

Abstract

The ore preparation technological complex control criteria considering the factors of energy efficiency, environmental and economic performance of mining factory are considered. Keywords: CONTROL CRITERIA, ORE PREPARATION, ENERGY EFFICIENCY, ENVIRONMENTAL AND ECONOMIC INDICATORS.

For the automated control formation, an ecological-economic system should be viewed as a hierarchical controlled dynamic system [1, 2].

However, it is necessary to take into account, that the important indicator of the mining enterprises effectiveness is the cost price and power consumption reduction of the raw iron ore extraction and processing technological processes [3-5, 12-14]. In modern conditions, on average of 5–8 ore technological varieties is processed on mining enterprises [6]. At the same time the mining operations system does not allow to produce the same type of ore long enough, which

leads to instability of raw mineral material composition which input to the beneficiation.

For solving the problem of energy-efficient ore beneficiation automated process control it is advisable to allocate such components: providing the timely information on iron ore characteristics in process streams and technological processes parameters optimization on the basis of the obtained data. Since the issues of iron ore raw materials characteristics operational control at various stages of its processing using modern methods are well studied in the works [5,8,12-23], it is advisable to explore the issue of ore preparation automated control optimization, considering energy, environmental and economic factors.

In general, for the automated control of mining enterprises organizational and technical processes is necessary to process $\overline{\psi} = \{\psi_i \mid i = 1...N_r\}$ tons of ore, which is represented by a N_r number of technological species and to provide a certain enterprise production volume contractual obligations $\Omega(\overline{\psi}) = \Omega^* \in [\Omega^{(l)}, \Omega^{(h)}]$ with a minimum amount of harmful emissions into the environment $\Theta(\Omega, \overline{\psi}, t) \rightarrow \min$ and maximum profit $Pf(\Omega, \overline{\psi}, t) \rightarrow \max$ at a certain time interval of t. In [7] proved, that for the assessment of enterprise environmental and economic performance it is useful to compare the value of its harmful effects, and profit from the iron-containing products production, which takes the following form, considering the need to redesign several varieties of iron ore

$$\frac{\Theta(\overline{\Omega}, \overline{\psi}, t)}{Pf(\overline{\Omega}, \overline{\psi}, t)} \to \min, \qquad (1)$$

where $\Theta(\overline{\Omega}, \overline{\psi}, t)$ – is the mining enterprise dust and gas emission in the interval of t, ton; $Pf(\overline{\Omega}, \overline{\psi}, t)$ – is the profit from the product sales on the interval of *t*, hrn.

The total mining enterprise dust and gas emission is defined by indicators of unorganized and organized dust and gas emission [7], thus it is necessary to take into account each of these parameters dependence on the amount of processed technological species

$$\Theta\left(\overline{\Omega}, \overline{\psi}, t\right) = \Theta'\left(\overline{\Omega}, \overline{\psi}, t\right) + \sum_{j=1}^{N_{\Theta}} \Theta''_{j}\left(\overline{\Omega}, \overline{\psi}, t\right) \quad (2)$$

where $\Theta'(\overline{\Omega}, \overline{\psi}, t)$ – is the organized dust emission in the interval of *t*, ton; $\Theta''_j(\overline{\Omega}, \overline{\psi}, t)$ – is the *j*unorganized dust emission rate in the interval of *t*, ton.

The mining factory production profit considering the results obtained in [7] in terms of processing several technological variations of ore is given by, UAH

$$Pf\left(\overline{\Omega}, \overline{\psi}, t\right) = \sum_{i=1}^{N_{\Omega}} \Omega_{i}\left(\overline{\psi}, t\right) \cdot \Pr_{\Omega_{i}}\left(\overline{\psi}, t\right) - \left[\sum_{i=1}^{N_{\Omega}} \Omega_{i}\left(\overline{\psi}, t\right) \cdot E_{\Omega_{i}}\left(\overline{\psi}, t\right)\right]$$
(3)

where $\Omega_i(\overline{\psi}, t)$ – is the *i*-th names production output amount in the interval of *t* considering processing volumes of individual technological varieties,ton;

 $\Pr_{\Omega i}(\overline{\psi}, t)$ – is the wholesale price of the *i*-th product names in the interval of *t*, hrn; N_{Ω} – is the number of the plant production names; $E_{\Omega i}(\overline{\psi}, t)$ – is the specific operating costs for the *i*-th name of the product, hrn/ton.

Considering the dependences (2) and (3) the ecological and economic efficiency criterion (1) of mining and processing plant which processing several ore technological types when optimizing the period consisting of T slots, will take the form

$$J_{\Theta}\left(\overline{\psi}\right) = \max_{t=1\sim T} \left\{ \frac{\left[\Theta'\left(\overline{\Omega}, \overline{\psi}, t\right)\right] + \sum_{j=1}^{N_{\Theta}} \left[\Theta''_{j}\left(\overline{\Omega}, \overline{\psi}, t\right)\right]}{\sum_{i=1}^{N_{\Omega}} \Omega_{i}\left(\overline{\psi}, t\right) \cdot \Pr_{\Omega_{i}}\left(\overline{\psi}, t\right) - \left[\sum_{i=1}^{N_{\Omega}} \Omega_{i}\left(\overline{\psi}, t\right) \cdot E_{\Omega_{i}}\left(t\right)\right]} \right\} \to \min, \qquad (4)$$

It should be noted that in the market relations conditions the volume, mineral content, wholesale price and other characteristics of the mining enterprises products rather rigidly limited to contractual obligations to consumers. In other words, to significantly reduce harmful emissions into the environment due to the decrease in production volumes is impractical.

To meet the energy efficiency terms, as well as beneficiation features outlined in [9], it is appropriate to use the following criteria proposed in [8]: concentrate residues amount minimization in stock, the process equipment utilization rate

© Metallurgical and Mining Industry, 2014, No. 5

maximizing, specific weight stabilization of each technological variety in the input stream.

It is necessary to consider the constraints posed by the technological process and mine raw ore limited supplies in the current period, the process equipment limited capacity and the preventive maintenance schedule, fixed in the contractual commitments concentrate amount and mineral content in it described in detail in [8]

Thus, the ore preparation generalized energy-efficient control criterion considering ecological and economic factors of the mining and processing plant activities it is advisable to form a conflict situations modeling device [11], taking into account the importance of each particular criterion.

References

- Ugolnitsky G. A. Upravleniye ekologoekonomicheskimi sistemami. Moscow: Vuzovskaya kniga, 1999.
- 2. Ugolnitsky G., Usov A. Matematicheskaya formalizatsiya metodov iyerarkhicheskogo upravleniya ekologo-ekonomicheskimi sistemami. Problemy upravleniya, no4 (2007): 64-69.
- Vilkul Yu., Temchenko A., Morkun V. Strategiya razvitiya gornometallurgicheskogo kompleksa Ukrainy: effektivnost proizvodstva i kachestvo produktsii. Gornyy zhurnal, no10 (2007): 77-82.
- Piven V., Shipovskiy G, Dyadechkin N. Ekonomicheskaya effektivnost povysheniya kachestva gornometallurgicheskogo syrya. Gornyy zhurnal, no9 (2003): 57-58.
- 5. Morkun V. Ultrazvukovoy kontrol kharakteristik izmelchennykh materialov i adaptivnoye upravleniye protsessami izmelcheniya-klassifikatsii rud na yego baze. ScD diss., Krivoy Rog, 1998.
- Kupin A. Uzgodzhene intelektualne keruvannya stadiyami tehnologichnogo processes zbagachennya magnetite kvartsitiv in minds neviznachenosti. ScD diss., Krivoy Rog, 2009.
- 7. Vilkul Yu. Opredeleniye parametrov gornykh predpriyatiy na osnove ikh ekologo-ekonomicheskikh pokazateley. ScD diss., Krivoy Rog, 1994.
- Tron V. Power efficient automatized control of ore-dressing process using thermographic recognition of ore's types. PhD diss., Krivoy Rog, 2003.

- Xiaoling H., Yangang C., Yi H., Tianyou C. Production Process Management System for Production Indices Optimization of Mineral Processing. China: IFAC, 2005.
- 10. Batishchev D. Shaposhnikov D. Mnogokriterialnyy vybor s uchetom individualnykh predpochteniy. Nizhny Novgorod: IPF RAN, 1994.
- 11. Saati T. Matematicheskiye modeli konfliktnykh situatsiy. Moscow: Sovetskoye radio, 1977.
- 12. Kachestvo mineralnogo syrya. Kryvyi Rih: Mineral, 2005.
- 13. Kochura Ye., Belkina I. Vpliv yakostí zaliznoyi rudi na sobivartist zalizorudnogo kontsentratu. Naukoviy visnuk NGU, no. 4 (2011): 120-126.
- 14. Piven V., Romanenko A., Shepel V. Issledovaniye vliyaniya koleblemosti kachestvennykh parametrov rudopotokov karyera na effektivnost obogashcheniya zheleznykh rud. Metallurgicheskaya i gornorudnaya promyshlennost, no.2, (2007): 67-71.
- 15. Morkun V. S., Morkun N. V., Pikilnyak A.V. Simulation of high-energy ultrasound propagation in heterogeneous medium using k-space method, Metallurgical and Mining Industry, 2014, No3, p.p. 23-27: http://www.metaljournal.com.ua/assets/Ar chive/en/MMI3/4.pdf
- 16. Morkun V. S., Morkun N. V., Pikilnyak A.V. Ultrasonic phased array parameters determination for the gas bubble size distribution control formation in the iron ore flotation, Metallurgical and Mining Industry, 2014, No3, p.p. 28-31: http://www.metaljournal.com.ua/assets/Ar chive/en/MMI3/5.pdf.
- 17. Morkun V., Morkun N., Pikilnyak A.The gas bubble size distribution control formation the in flotation process,*Metallurgical* and Mining No4. 42-45: Industry, 2014, p.p. http://www.metaljournal.com.ua/assets/Jou rnal/9.2014.pdf.
- V. Morkun, N. Morkun, A. Pikilnyak. The study of volume ultrasonic waves propagation in the gas-containing iron ore pulp, Ultrasonics, No 56C, (2015): 340-343.
- 19. Bastan P., Kostina N. Smeshivaniye i sortirovka rud. Moscow: Nedra, 1990.

- 20. Nesterov G. Tekhnologicheskaya optimizatsiya obogatitelnykh fabrik. Moscow Nedra, 1976.
- 21. Azaryan A., Azaryan V., Lisovoy G. Sostoyaniye problemy kontrolya kachestva pri dobyche i pererabotke zhelezorudnogo syrya. Girnichiy visnik, no.95, (2012): 132-136.
- 22. Konstantinov G. Development of quality management system in the processing of iron ore. PhD diss., Krivoy Rog, 2000.
- 23. Porkuyan O. Keruvannya nelíníynimi dinamíchnimi obektami zbagachuvalnikh virobnitstv na osnovi gibridnikh modeley Gamershteyna. ScD diss., Krivoy Rog, 2009